



Ref. Certif. No.

JPTUV-162568

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE) CB SCHEME

CB TEST CERTIFICATE

Product

AC EV Charger

Name and address of the applicant

Jiangsu Acrel Electric Energy Service Co., Ltd
31 Hongtu Road, Nanzha Street, Jiangyin City, Wuxi City,
214405 Jiangsu
P.R. China

Name and address of the manufacturer

Jiangsu Acrel Electric Energy Service Co., Ltd
31 Hongtu Road, Nanzha Street, Jiangyin City, Wuxi City,
214405 Jiangsu
P.R. China

Name and address of the factory

Note: When more than one factory, please report on page 2

Jiangsu Acrel Electric Energy Service Co., Ltd
31 Hongtu Road, Nanzha Street, Jiangyin City, Wuxi City,
214405 Jiangsu
P.R. China

Ratings and principal characteristics

Refer to Page 2

Trademark / Brand (if any)

ACREL (LOGO)

Customer's Testing Facility (CTF) Stage used

N/A

Model / Type Ref.

AEV300-AC007D-EU-01 ; AEV300-AC007D-EU-02
AEV300-AC007D-EU-03 ; AEV300-AC007D-EU-04
AEV300-AC007D-EU-05 ; AEV300-AC007D-EU-06
AEV300-AC007D-EU-07 ; AEV300-AC007D-EU-08

Additional information (if necessary may also be reported on page 2)

See additional page(s) for further Additional information.
Detail information refer to test report CN24JM58 001

A sample of the product was tested and found to be in conformity with

IEC 61851-1:2017

As shown in the Test Report Ref. No. which forms part of this Certificate

CN24JM58 001

This CB Test Certificate is issued by the National Certification Body



TÜV Rheinland Japan Ltd.
4-25-2 Kita-Yamata, Tsuzuki-ku
Yokohama 224-0021, Japan
Mail: info@jpn.tuv.com

Date: 2024-07-29

Signature: Dipl.-Ing. (FH) Fan He

10/061SMD 2022-07 rke-fix

Additional information :

AEV300-AC007D-EU-01 ; AEV300-AC007D-EU-02
AEV300-AC007D-EU-03 ; AEV300-AC007D-EU-04
AEV300-AC007D-EU-05 ; AEV300-AC007D-EU-06
AEV300-AC007D-EU-07 ; AEV300-AC007D-EU-08

Input : 230V a.c., 1P+N+PE,
50/60Hz, 32 A a.c.
Output : 230V a.c., 1P+N+PE,
50/60Hz, 32 A a.c., 7kW
Type of EV connection: Case C (Connector)
Operating temperature: -30 °C to 50 °C
Protection level : IP54



Date: 2024-07-29

Signature: as on page 1